



>> KEY FEATURES	
Light Colour: Amber	Additional: Cable with switch included
• Lens: Clear	• Dimensions: 1500mm x 100mm x 45mm
Fixing: Bolt Bracket	Tough polycarbonate lens with UV resistance
Approval: ECE R10/R65 Approved	Aluminium base
Voltage: 12-24V	Reverse polarity protection
IP Rating: IP67	Clear Lens
• LEDs: 252	
Patterns: 27 Selectable Flash Patterns	 -30°C to +60°C operating temperature

FOR MORE INFORMATION, CONTACT OUR SALES TEAM. T: 020 8863 8333 (OPT1) • E: sales@c-ko.co.uk • W: www.c-ko.co.uk





Amber Light Bar 1500mm Bolt Mounted

Wiring Information

- Red: Power
- Black: Ground
- Yellow: Flash Pattern Programming / Dimming
- White: Synchronisation connect to other light bar
- Blue: Middle to side arrowstick connect to red permanently
- Brown: Right arrowstick connect to red permanently
- Green: Left arrowstick connect to red permanently

>> Flash Pattern Information

Tap yellow wire to red wire for under 1 second to change to next pattern, 1-3 seconds for previous pattern and over 5 seconds to activate 50% dimming function, repeat 5 the over 5 second tap on red wire to disengage the dimming function.

- 1. Single R65
- 2. Double R65
- 3. Triple
- 4. Quad R65
- 5. Single Slow
- 6. Single Half to Half R65
- 7. Double Half to Half R65
- 8. Triple Half to Half
- 9. Quad Half to Half
- **10.** Half to Half + All
- 11. Single + Quad
- 12. Right Arrowstick
- 13. Left Arrowstick
- 14. Middle to Side Arrowstick

Right Constant
 Left Constant
 Middle to Side Constant
 One - One Eight Fast
 One - One Single
 One - One Single - Split Accelerate
 Centre Out Quad
 Centre Out Single - Split Accelerate
 End Octa - Half to Half
 Out Steady On - Centre Double
 One Steady On - One Single
 Cycle (6,19,9,18,21,2)
 Steady On



Warning: Avoid looking directly at LEDs while they are in operation. Doing so may result in temporary vision impairment or permanent eye damage.

FOR MORE INFORMATION, CONTACT OUR SALES TEAM.

T: 020 8863 8333 (OPT1) • E: sales@c-ko.co.uk • W: www.c-ko.co.uk

